2011

High Conductivity Solid Oxide Electrolyte Composite-Laminates Utilizing Scandia/Ceria Co-Doped Zirconia Core with Yttria Stabilized Zirconia Outer Skins

Jay Neutzler

University of South Carolina - Columbia, neutzler@email.sc.edu

Xinyu Huang

University of South Carolina - Columbia, xyhuang@sc.edu

Joshua Sightler

Yan Chen

Nina Orlovskaya

Follow this and additional works at: https://scholarcommons.sc.edu/emec_facpub

Part of the [Electro-Mechanical Systems Commons](#), [Manufacturing Commons](#), and the [Materials Science and Engineering Commons](#)

Publication Info

Postprint version. Published in *ECS Meeting Abstracts*, Issue 1824, 2011.

© ECS Meeting Abstracts, 2011, The Electrochemical Society

Neutzler, J., Huang, X., Sightler, J., Chen, Y., Orlovskaya, N. (2011). High Conductivity Solid Oxide Electrolyte Composite-Laminates Utilizing Scandia/Ceria Co-Doped Zirconia Core with Yttria Stabilized Zirconia Outer Skins. *ECS Meeting Abstracts*, 1824.

This Article is brought to you by the Mechanical Engineering, Department of at Scholar Commons. It has been accepted for inclusion in Faculty Publications by an authorized administrator of Scholar Commons. For more information, please contact digres@mailbox.sc.edu.

High conductivity solid oxide electrolyte composite-laminates utilizing Scandia/Ceria co-doped Zirconia core with Yttria Stabilized Zirconia outer skins

Jay Neutzler¹, Xinyu Huang¹, Joshua Sightler¹, Yan Chen², Nina Orlovskaya²

¹University of South Carolina
Dept. of Mechanical Engineering and SOFC Program,
300 Main Street, Columbia, SC 29208, USA

²University of Central Florida
Dept. of Mechanical Materials & Aerospace Engineering
Orlando, FL 32816

Increasing the conductivity of electrolytes in lower temperature Solid Oxide Fuel Cells (SOFC) is of great importance. However, there are several challenges that are to be addressed, which include phase stability of electrolyte’s crystal structure, chemical stability in both oxidizing and reducing environments, and maintaining mechanical integrity and high ionic conductivity over time.

Scandia-Ceria-Zirconia ($(\text{Sc}_2\text{O}_3)_{0.10}(\text{CeO}_2)_{0.01}(\text{ZrO}_2)_{0.89}$ —(10Sc1CeSZ) is an excellent lower temperature SOFC electrolyte. The phase stability of 10Sc1CeSZ was studied in [1,2] and it was found that the cubic phase is stable across room to operation temperatures when not dwelling at ~350-400°C for several hours, where the β rhombohedral phase of 10Sc1CeSZ becomes a stable structure. However, chemical stability with “aging” has been of concern and recent studies by S. Omar, et al. [3], exemplify the degradation. Yttria Stabilized Zirconia (YSZ) has lower conductivity than ScSZ, but is widely accepted as a more stable electrolyte material.

The authors have fabricated laminated composites of Scandia/Ceria co-doped Zirconium Oxide (ScCeSZ) and Yttria Stabilized Zirconia (YSZ) produced by tape casting techniques. Green tapes of individual 10Sc1CeSZ and 8 mol% (8YSZ) electrolytes were first produced. Laminates of 3, 4, and 6 layer electrolytes tapes were laminated and then fired. In the composite laminated electrolytes, the 8YSZ was used as the outer-layers and the 10Sc1CeSZ was used as core layers. The conductivity and aging behavior of the laminate electrolytes were studied.

Conductivity testing of the laminated electrolytes using Electrochemical Impedance Spectroscopy (EIS) was carried out in a temperature range of 500-800°C. Impedance results on electrolyte samples have clearly resolved the bulk resistance through Nyquist plots. Arrhenius plots of each design of the electrolyte were constructed from the temperature profiles. The data shows consistent conductivity performance groupings of the base materials (8YSZ and 10Sc1CeSZ) in 3, 4, and 6 layer configurations (Figure 1). When utilizing 3, 4, and 6 layer composite laminations (outer-core-outer layers of YSZ-ScCeSZ-YSZ, respectively), there appears to be good correlation of conductivity with laminate volumetric content (Figure 2).

Aging experiment of the composite electrolyte was also conducted in different gas environments. The results of conductivity and the “aging” studies and the degree that composite laminate lay-ups of YSZ-ScCeSZ-YSZ will

mitigate degradation will be discussed.

Figure 1: Laminate comparisons for 3, 4, & 6 layers of 8YSZ and 10Sc1CeSZ.

Figure 2: YSZ-ScCeSZ-YSZ Composite Laminate comparisons for 3, 4, & 6 layers with 6 layer 8YSZ and 10Sc1CeSZ.

References:

- [1] S. Yarmolenko, J. Sankar, N. Bernier, et al., Phase Stability and Sintering Behavior of 10 mol % Sc₂O₃-1 mol %CeO₂-ZrO₂ Ceramics, Journal of Fuel Cell Science and Technology, 2009, Vol. 6, Issue 2, Article No. 021007.
- [2] S. Lukich, C. Carpenter, N. Orlovskaya, Temperature and stress induced changes of the vibrational response of cubic and rhombohedral 10 mol% Sc₂O₃ – 1 mol% CeO₂ – ZrO₂ ceramics, Journal of Power Sources, April 15, 2010, Vol. 195, Issue 8, pp. 2301-2309.
- [3] S. Omar, A. Belda, A. Escardino, N. Bonanos, Ionic conductivity ageing investigation of 1Ce10ScSZ in different partial pressures of oxygen, Solid State Ionics, March 3, 2011, Vol. 184, Issue 1, pp. 2-5.